



TECHNICAL DATA SHEET No 703

S115 AUTO SEAL CARTRIDGE

GENERAL TECHNICAL DESCRIPTION

Rubber-based seam sealer with water- and soundproof properties.

Remains permanently elastic.

Resistant to chemicals, mechanical stress and to temperatures from -25°C to 80°C (-13°F to 176°F).

It can be overpainted with any HB BODY paint system.

Fast drying.

SURFACE

Inside or bottom parts of the car body

PRETREATMENT/CLEANING OF SUBSTRATE



The surface to be coated must be dry, clean, and free of grease and other contaminants. Ensure all substrates are thoroughly cleaned and dried at every step of the preparation process.

PRODUCT APPLICATION



Apply using the cartridge applicator



3 h / 23°C (73°F)
200 µm (7.9 mil)



It can be painted over with all HB BODY paint systems, starting 15 min after application, up to 60 min at 23°C (73°F) or after drying.

Note: For maximum adhesion, it is recommended to apply P340 PLASTOFIX, prior to painting. Please refer to the relevant Technical Data Sheet for application guidance.

SPECIFIC GRAVITY

1.2 ± 0.1 g/cm³

SOLID CONTENT

63 ± 2% Weight

VOC (2004/42/EC)

This product is a special refinishing product based on its ingredients

and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 840 g/L.

2004/42/IIIB(e)(840)840

CLEANING OF EQUIPMENT

Clean after final use with 767 NITRO thinner / reducer.

REMARKS

- Optimum operating temperature range 20 - 30°C (68 - 86°F).
- Drying time depends on film thickness and ambient temperature.

STORAGE SHELF LIFE

Guaranteed shelf life of 24 months in unused original containers stored in a cool place (5 - 25°C) (41 - 77°F).



Always wear protective equipment



Follow the application instructions mentioned in this TDS

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

JULY 2025